

15W Network Wooden Speaker NS-W015

1. High-fidelity 15W speaker with 16-bit stereo CD-quality sound.
2. Two-way intercom communication
3. SIP protocol compatible, integration with VoIP and IPPBX systems
4. Dual SIP accounts, supports Direct IP Call and RTP Multicast
5. Wall-mount design with durable fiberboard, operating -20°C to +60°C.
6. Ideal for indoor public address systems



Specification:

Networking

Interface	10/100 Base-TX, RJ45
Supported Protocols	SIP, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP
Security	Password protection, IP address filtering, Digest authentication, User access log

Audio

Rated Power	15W
MAX SPL	99dB
Frequency Response	150 Hz – 16 kHz
Total Harmonic Distortion	≤0.3%
Signal-to-Noise Ratio	> 70 dB
Decoding	OPUS 48KHz, MP3 44.1KHz, G.722-ADPCM 16KHz, G.711-PCMU 8KHz, G.711-PCMA 8KHz, G726 8KHz, GSM 8KHz, LPCM-16bit-Stereo/Mono 44.1kHz
Built-in MIC	YES

VoIP

Protocol	SIP (compatible with VoIP, SIP devices such as IPPBX, IP Phone)
Functions	2 SIP Accounts SIP Direct IP Call, RTP Multicast
Codecs	OPUS, G722, G711U, G711A

General

Dimensions	250 × 170 × 160 mm
Power Supply	PoE or DC 12V
Interface	RJ45, DC Power Input, GPIO Alarm Input, Reset Button
Enclosure Material	Fiberboard
Weight	1.5 kg
Operating Temp	-20°C ~ +60°C
Installation	Wall mount
Package Includes	Network Wall Speaker, Quick Star Guide