

30W IP Horn Speaker NS-H030

1. 30W high-power output with long-distance sound coverage
2. Clear, bright sound with strong penetration
3. Supports multiple audio codecs (OPUS, G722, G711U, G711A)
4. SIP protocol compatible, integration with VoIP and IPPBX systems
5. Dual SIP accounts, supports Direct IP Call and RTP Multicast
6. Durable ABS housing, Poe power supply



Specification:

Networking

Interface	10/100 Base-TX, RJ45
Supported Protocols	SIP, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP
Security	Password protection, IP address filtering, Digest authentication, User access log

Audio

Rated Power	30W
MAX SPL	122dB
Frequency Response	400 Hz – 6 kHz
Decoding	OPUS 48KHz, MP3 44.1KHz, G.722-ADPCM 16KHz, G.711-PCMU 8KHz, G.711-PCMA 8KHz, G726 8KHz, GSM 8KHz, LPCM-16bit-Stereo/Mono 44.1kHz

VoIP

Protocol	SIP (compatible with VoIP, SIP devices such as IPPBX, IP Phone)
Functions	2 SIP Accounts SIP Direct IP Call, RTP Multicast
Codecs	OPUS, G722, G711U, G711A

General

Dimensions (H x W x D)	285 × 205 × 280 mm
Power Supply	PoE or DC 24V
Interface	RJ45, DC Power Input, GPIO Alarm Input, Reset Button
Enclosure Material	ABS
Weight	1.8 kg
Installation	Wall Mounted
Package Includes	Network Horn Speaker Quick Star Guide